

Cat6 23-4pr UTP CMX Direct Burial



Cat6 UTP CMX Direct Burial 23awg solid copper 4pair unshielded, twisted pairs, PE insulated, Gel Filled Core Black CMX rated PE Jacket. The cable meets all the ANSI/TIA.EIA-568-B.2 specifications

Specifications and Compliance:

- CSA C22.2 No. 214-08
- NFPA 262 ANSI/TIA-568-C.2
- ANSI/ICEA S-90-661-2021 Article 800
- NEC (NFPA 70) Industry compliances

RW Item No.	No. of Pairs	Solid Cu AWG	Nominal Diameter (mm)	Nominal Impedance (ohms)	Nominal Velocity of Prop. (%)	Approx Weight Weight (kg/km)
TEE23-04-CAT6-V-305	4	23	5.1	100 (+/-15)	71	41

Colour Coding

- Blue & white/blue stripe
- Orange & white/orange stripe
- Green & white/green stripe
- Brown & white/brown stripe

Features

- High Performance exceeding Cat5e Specifications
- Gel filled core water blocking
- Black S/R-Sun Resistant LLDPE Jacket

Application

- 10BASE-T through 1000BASE-T Ethernet
- Power over Ethernet (PoE)
- IEEE 802.3af PoE+
- IEEE 802.3at Type 1 and 2 ATM and token ring
- Outdoor/burial LAN Network Cable

All dimensions are nominal and are subject to normal manufacturing tolerance. Specifications are subject to change without notice.

