

SHIPBOARD CABLE 2.5mm²-2c LSZH 1KV



2C 2.5 MM² (14 AWG) BARE COPPER, XLPE Insulation, 5 mil thick fiber glass tape, black sun resistant, low smoke zero halogen jacket, Suitable for use in 90C WET/DRY

Specifications and Compliance

Lloyd's Register, ABS & Transport Canada approved, IEC 60092-350, IEC 60754-1, IEC 61034-1&2, IEC 60092-376 SF# SE010E5A02F0801

Flame Propagation Test Rating: IEC 60332-3-22 Category 'A'

RW Item Number	Cond. Guage In mm ²	Copper Conductor Stranding Class 5	Insulation Thickness Inches	Diameter of Conductor Inches	Average Outer Jacket Thickness Inches	Nominal Overall Cable Dia. Inches	Nominal Overall Cable Weight Kg/Km
MARNZ-2.5MM-2C	2.5	50x.009"	0.028	0.137	0.045	0.390	138

Ampacity @ 45 °C (Amps)	Max. DC Cond. Res. Ohms/ MFT @ 25 °C	Capacitance Conductor to Conductor Pf/ft	Max. Pulling Tension Pulling Grips LBS	Max. Pulling Tension Pulling Eyes LBS	Min. Bending Radius Permanent Inches	Min. Bending Radius Pulling Inches	Nominal Cable Lay Inches
26	2.531	14.6	49	75	2.3	3.5	1.0

Ampacity value based on ABS Rules for Building and Classing Steel Vessels, Version 2009, Table-6. Values are corrected according to Table-6 for number of Conductors

Colour Code

- 2C- Brown & blue

Features

- Rated at 90°C wet & dry
- 35C Cold Impact, -40C Cold Bend
- Low smoke-zero halogen jacket
- Transport Canada Approved

Application

- Power, communication, control, lighting, electronic, instrumentation, and special-purpose applications in shipboard applications